



Specifications	
Operating Weight (kg)	6065
Engine Power (kW/rpm)	43.3/2400
Standard Bucket Capacity (m ³)	0.25
Standard Bucket Width (with side cutters) (mm)	760
Performance	
Travel Speed (Low/High) (km/h)	2.5/5.0
Swing Speed (rpm)	11
Ground Pressure (kPa)	32
Gradeability (o)	35
Maximum Arm Crowd Fore (kN)	28
Maximum Bucket Digging Force (kN)	40
Equipments	
Engine Model	Yanmar 4TNV94L-PLY
Displacement (L)	3.054
Swing Device Driving Type	Hydraulic drive
Travel Device Driving Type	Hydraulic Drive

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck

Brake Type	Hydraulic Lock
Standard Track Shoe Type	Triple Grouser Shoes
Track Adjustment Device	Grease Tension
Hydraulic Pump Type	Variable Piston Pump
Maximum Setting Pressure Traveling (MPa)	27.5
Working (MPa)	24.5
Implement	
Boom Length (mm)	3000
Arm Length (mm)	1550
Bucket Radius (mm)	R937
Refill Capacity	
Fuel (diesel) (L)	90
Hydraulic oil (Refilling) (L)	115
Battery Capacity	85AH

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck