



| Specifications | |
|--|--------------------|
| Operating Weight (kg) | 8200 |
| Engine Power (kW/rpm) | 57.7/2200 |
| Standard Bucket Capacity (m ³) | 0.34 |
| Standard Bucket Volume Range (m ³) | 0.11-0.42 |
| Performance | |
| Travel Speed (Low/High) (km/h) | 2.8/5.4 |
| Swing Speed (rpm) | 12.2 |
| Ground Pressure (kPa) | 34 |
| Gradeability (o) | 35 |
| Maximum Arm Crowd Fore (kN) | 39.6 |
| Maximum Bucket Digging Force (kN) | 51.2 |
| Equipments | |
| Engine Model | Yanmar 4TNV98T-SFN |
| Displacement (L) | 3.319 |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck

| | |
|--|----------------------|
| Swing Device Driving Type Hydraulic Drive | |
| Travel Device Driving Type Hydraulic Drive | |
| Brake Type | Hydraulic Lock |
| Standard Track Shoe Type | Triple Grouser Shoes |
| Track Adjustment Device | Grease Tension |
| Hydraulic Pump Type | Variable Piston Pump |
| Maximum Setting Pressure Traveling (MPa) | 28.5 |
| Working (MPa) | 28.5 |
| Implement | |
| Boom Length (mm) | 3720 |
| Arm Length (mm) | 1665 |
| Bucket Radius (mm) | R1008 |
| Refill Capacity | |
| Fuel (diesel) (L) | 146 |
| Hydraulic oil (Refilling) (L) | 120 |
| Battery Capacity | 85AH |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck