



Specifications	
Operating Weight (kg)	14000
Engine Power (kW/rpm)	86/2200
Standard Bucket Capacity (m ³)	0.56
Standard Bucket Width (with side cutters) (mm)	875
Performance	
Travel Speed (Low/High) (km/h)	3.34/5.5
Swing Speed (rpm)	11.9
Ground Pressure (kPa)	45
Gradeability (o)	35
Maximum Arm Crowd Fore (kN)	65
Maximum Bucket Digging Force (kN) 85	
Equipments	
Engine Model	Cummins B3.9-C
Displacement (L)	3.9
Swing Device Driving Type Hydraulic Drive	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck

Travel Device Driving Type Hydraulic Drive	
Brake Type	Hydraulic Lock
Standard Track Shoe Type	Triple Grouser Shoes
Track Adjustment Device	Grease Tension
Hydraulic Pump Type	Variable Piston Pump
Maximum Setting Pressure Traveling (MPa)	34.3
Working (MPa)	34.3
Implement	
Boom Length (mm)	4600
Arm Length (mm)	2500
Bucket Radius (mm)	R1270
Refill Capacity	
Fuel (diesel) (L)	270
Hydraulic oil (Refilling) (L)	159
Battery Capacity	2×120AH

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck