



Principal dimension	
Operating Weight(kg)	1500
Standard Bucket Capacity (m ³)	0.07
Size of blade(mm)	990×240
Overall Length (trans pos)(mm)	3688
Overall Width (trans pos) (mm)	1014
Overall Height (trans pos) (mm)	2255
Wheel Base(mm)	1045
Length Of Track(mm)	1405
Width Of Track(mm)	230(rubber)
Clearnce under Counterweight (mm)	462
Ground Clearance (mm)	213
Tail Turning Radius(mm)	1165
Operating envelope	
Maximum Digging Height(mm)	3170
Maximum Digging Depth(mm)	2060
Maximum Dumping Height(mm)	1785

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck

Maximum Vertical Digging Dist.(mm)	1802
Minimum Turning Radius(mm)	1694
Maximum Digging Dist.(mm)	3697
Maximum Ground Digging Dist.(mm)	3626
Engine	
Engine Model	Laidong LL380B
Rated Power(kw/rpm)	13.6/2200
Max. torque(N.m/rpm)	67.9/1450~1650
Displacement(L)	1.36
hydraulic system	
Main pump rated flow(L/min)	41.8
Main pump rated speed(rpm)	2200
Working device circuit(Mpa)	16
Travel Circuit(Mpa)	16
Swing Circuit (Mpa)	12.5
Characteristic	
Maximum Gradeability(°)	30
Travelling Speed(km/h)	2
Swing speed(rpm)	10~12
Ground Pressure(Kpa)	≤27
Maximum traction(KN)	7.7
Bucket digging force (KN)	8.8
Arm digging force(KN)	6.2

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck