



Principal dimension	
Operating Weight(kg)	2040
Standard Bucket Capacity (m ³)	0.09
Size of blade(mm)	1270×210
Overall Length (trans pos)(mm)	4080
Overall Width (trans pos) (mm)	1260
Overall Height (trans pos) (mm)	2330
Wheel Base(mm)	1220
Length Of Track(mm)	1584
Width Of Track(mm)	250(rubber)
Clearnce under Counterweight (mm)	497
Ground Clearance (mm)	231
Tail Turning Radius(mm)	1201
Operating envelope	
Maximum Digging Height(mm)	3740
Maximum Digging Depth(mm)	2620
Maximum Dumping Height(mm)	2250
Maximum Vertical Digging Dist.(mm)	2261

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck

Minimum Turning Radius(mm)	1860
Maximum Digging Dist.(mm)	4270
Maximum Ground Digging Dist.(mm)	4180
Engine	
Engine Model	Changchai ZN390G
Rated Power(kw/rpm)	20/2200
Max. torque(N.m/rpm)	100/1500
Displacement(L)	1.813
hydraulic system	
Main pump rated flow(L/min)	59.4
Main pump rated speed(rpm)	2500
Working device circuit(Mpa)	16
Travel Circuit(Mpa)	16
Swing Circuit (Mpa)	12
Characteristic	
Maximum Gradeability(°)	30
Travelling Speed(km/h)	2.5
Swing speed(rpm)	10~12
Ground Pressure(Kpa)	30.2
Maximum traction(KN)	9
Bucket digging force (KN)	14.8
Arm digging force(KN)	11.5

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck