



Model		HDT5256GJB (12336)	HDT5256GJB1 (12336)
		HDT5256GJB (12375)	HDT5256GJB1 (12375)
Whole Vehicle Performance & Parameters	Chassis	HOWO	STEYR KING
	Curb Weight (Kg)	15000	15000
	Total Vehicle Weight (Kg)	25000	25000
	Outline Dimension(L*B*H) (mm)	9880*2496*3920	9800*2496*3880
	Wheelbase (mm)	4025+1350	4000+1350
	Front Overhang (mm)	1500	1560
	Rear Overhang (mm)	2980	2890
	Min. Clearance Above Ground(mm)	245	296
	Max. Traveling Speed (km/h)	86	90
	Min. Turning Diameter (M)	20	19.3
	Oil Consumption per 100 km(under limited conditions)	≤25	≤25
Vehicle	Clutch	Dry Single Disc Clutch	Dry Single Disc Clutch (φ430)

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck

Configuration		($\phi 430$)	
	Gear Box	ZF5S-150GB	HW18709
	Driving Type	6*4	6*4
	Steering Mechanism	ZF8098	ZF8098
	Service Brake	Dual-circuit Air Brake	Dual-circuit Air Brake
	Parking Braking	Spring-powered Air-cut-off Brake	Spring-powered Air-cut-off Brake
	Auxiliary Brake	Engine Exhaust Brake	Engine Exhaust Brake
	Tyre	12.00(R)-20	12.00(R)-20
Engine Parameters	Model	P11C-UH;WD615.95	WD615.95,WD615.95E,WD615.96,WD615.96E
	Type	In-line 6-cylinder, Water-cooled, Supercharged, Inter-cooled, Electric (Direct) Injection Diesel Engine or EGR	In-line 6-cylinder, Water-cooled, Supercharged, Inter-cooled, Electric (Direct) Injection Diesel Engine or EGR
	Emission Standard	China III, Euro III	China III, Euro III
	Power (KW) Max Torque	336HP, 375HP (2200r/min) 1420,1350 N.m	336HP, 375HP (2200r/min) 1420,1350 N.m
Mixing Drum Parameters	Geometric Volume of Mixing Drum (m^3)	18.5	18.5
	Max Mixing Cubage (m^3)	12-13	12-13
	Feeding Speed (m^3)	≥ 3.5	≥ 3.5
	Discharging Speed ($\geq m^3$)	≥ 2.5	≥ 2.5
	Leftover Rate	Nearly Zero	Nearly Zero
	Max Rotating Speed (r/min)	14-16	14-16
Driving System	Mixing Drum Obliquity ($^{\circ}$)	12	12
	Max Mixing Drum Diameter (mm)	$\phi 2412$	$\phi 2412$
	Speed Reducer	Italian BONFILI-580	Italian BONFILI-580
	Hydraulic Pump	US EATON6423-279	US EATON6423-279
Driving System	Hydraulic Motor	US EATON6433-042	US EATON6433-042
	Radiator	German AKG with Vacuum Meter	German AKG with Vacuum Meter
Water Supply System	Water Tank Capacity (L)	260	260
	Water Supply Mode	Water Pump; Pneumatic Pump	Water Pump; Pneumatic Pump

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck