



Crawler Excavator LGE210LC

| | |
|------------------------------|--------------------------------|
| Engine | |
| Model | Cummins 6BTA5.9-C173(UK) |
| Type | Direct injection, water cooled |
| Rated power | 126kw |
| Rated speed | 2200rpm |
| Main Technical Specification | |
| Operating weight | 21000kg |
| Standard bucket capacity | 0.9m ³ |
| Slewing speed | 13rpm |
| Stick digging force | 102.5KN |
| Bucket digging force | 120.5KN |
| Hydraulic System | |
| Main pump | KAWASAKI |
| Main valve | TOSHIBA/Parker |
| Motor | TOSHIBA/Parker |
| Hydraulic flow rate | 2x235L/min |
| Hydraulic pressure | 30Mpa |
| Traveling System | |
| Traveling speed | 3-5Km/h |
| Grade ability | 65% |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

| | |
|--------------------------------|----------|
| Ground pressure | 0.042Mpa |
| Dimensions | |
| Overall length | 9760mm |
| Overall width | 3000mm |
| Overall height of boom | 3280mm |
| Overall height of cab | 2755mm |
| Engine cover height | 2300mm |
| Counterweight clearance | 1060mm |
| Ground clearance | 465mm |
| Upperstructure width | 2710mm |
| Rear-end length/Slewing radius | 2940mm |
| Overall track length | 4510mm |
| Track length of ground | 3720mm |
| Track gauge | 2400mm |
| Track width | 600mm |
| Boom slewing angle(L/R) | 0° |
| Operating Scope | |
| Stick length | 2920mm |
| A:Max cutting height | 9228mm |
| B:Max dumping height | 6410mm |
| C:Max digging depth | 6540mm |
| D:Max reach | 10000mm |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572