



Max. paving width	mm	6000	Screw diameter	mm	340
Max. paving thickness	mm	250	Screed extension		Hydraulic,mechanical
theoretical output	t/h	300	Basic width	mm	2800
Paving speed	m/min	3.07-9.16	Vibrator amplitude	mm	/
Travel speed	km/h	2.30-16.84	Vibrator strike times	time/min	/
Driving manner		Mechanical	Screed vibrator frequency	Hz	0-50
Overall weight	t	12-14	Screed heating method		Fuel heating, automatic ignition
Engine model and power		F6L913TDEUTZ,86 KW	Fuel tank capacity	L	200
Track shoe width	mm	Wheel type	Hydraulic oil tank capacity	L	150
Hopper capacity	t	12	Centralized lubrication		Made in China
Automatic leveling		Made in China	Material level instrument		/

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: [www.shlongji.com](http://www.shlongji.com) Wheel Loader,Road Roller,Dump Truck