



Max. paving width	mm	7000	Screw diameter	mm	Φ350
Max. paving thickness	mm	300	Screed extension		Hydraulic,mechanical
theoretical output	t/h	400	Basic width	mm	3000
Paving speed	m/min	2.00-3.60	Vibrator amplitude	mm	5
Travel speed	km/h	0.90-2.86	Vibrator strike times	time/min	0-1250
Driving manner		Mechanical	Screed vibrator frequency	Hz	0-33.3
Overall weight	t	16-19.5	Screed heating method		Fuel heating, automatic ignition
Engine model and power		BF6L913DEUT Z,86KW	Fuel tank capacity	L	190
Track shoe width	mm	300	Hydraulic oil tank capacity	L	210
Hopper capacity	t	12	Centralized lubrication		Made in China
Automatic leveling		Made in China	Material level instrument		

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: [www.shlongji.com](http://www.shlongji.com) Wheel Loader,Road Roller,Dump Truck