

## LGR210H Single Drum Vibratory Roller(Hydraulic Transmission)

LGR210H road roller is equipped with Cummins 6BT5.9 engine, SAUER or REXROTH hydraulic pump and motor, which introduced high-tech. hydraulic drive and vibratory. It is suitable for compaction of non-cohesive materials such as gravel, crushed stone, sand-macadam mixture, sandy soil and rock filling etc, base course, sub-base and embankment fill construction, which are ideal equipment for high-class highway, airport, harbors, dams and large-scale industrial ground.

| Engine                        |  |
|-------------------------------|--|
| Model                         | Cummins6BT5.9                            |
| Туре                          | Vertical, water cooled, direct injection |
| Rated power                   | 110KW                                    |
| Rated speed                   | 2200rpm                                  |
| Rated fuel consumption        | 210g/kw⋅h                                |
| Main Technical Specification  |  |
| Operating weight              | 10000kg                                  |
| Туре                          | Hydraulic vibration                      |
| Frequency                     | 29/35Hz                                  |
| Amplitude                     | 0.9/1.8mm                                |
| Static linear load            | 285N/cm                                  |
| Drum shell thickness          | 24mm                                     |
| Centrifugal force(high ampl.) | 240KN                                    |
| Centrifugal force(low ampl.)  | 120KN                                    |
| Working pressure              | 42Mpa                                    |
| Transmission System           |  |
| Туре                          | Hydraulic drive                          |
| Grade ability                 | 35%                                      |

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

| Traveling speed(km/h)       |  |
|-----------------------------|--|
| Forward/Reverse             | 0-12                                     |
| Traveling pump              | SAUER/REXROTH piston pump                |
| Traveling motor             | SAUER/REXROTH piston motor               |
| Axle                        | •  |
| Drive type                  | Dual wheel drive                         |
| Front axle load             | 5500kg                                   |
| Rear axle load              | 4500kg                                   |
| Steering System             |  |
| Туре                        | Articulated frame, hydraulic steering    |
| Steering cylinder           | Two cylinders                            |
| Steering pump               | Gear pump                                |
| Working pressure            | 13MPa                                    |
| Steering angle              | ±35°                                     |
| Min. steering radius        | 6500mm ( outer side),5400mm (inner side) |
| Braking System              |  |
| Service brake               | Oil-cut off braking                      |
| Parking brake               | Hand operated drum brake                 |
| Dimensions                  |  |
| Overall length              | 5820mm                                   |
| Overall width               | 2278mm                                   |
| Overall height              | 3050mm                                   |
| Drum width                  | 2100mm                                   |
| Wheel base                  | 3160mm                                   |
| Drum Dia.                   | 1570mm                                   |
| Tyre size                   | 17.5-25                                  |
| Ground clearance            | 472mm                                    |
| Service Capacities          |  |
| Hydrauclic tank             | 180L                                     |
| Drive alxe central gear box | 25L                                      |
| Fuel tank                   | 200L                                     |
| Engine crank case           | 19L                                      |