

## LGR212H-II Single Drum Vibratory Roller(Hydraulic Transmission)

LGR212H-II road roller is equipped with Cummins 6BT5.9 engine, SAUER or REXROTH hydraulic pump and motor, which introduced high-tech. full hydraulic drive and vibratory. It is suitable for compaction of non-cohesive materials such as gravel, crushed stone, sand-macadam mixture, sandy soil and rock filling etc, base course, sub-base and embankment fill construction, which are ideal equipment for high-class highway, airport, harbors, dams and large-scale industrial ground.

Cummins6BT5.9
Vertical, water cooled, direct injection
110KW
2200rpm
210g/kw∙h
12000kg
Hydraulic vibration
29/35Hz
0.9/1.8mm
1300N/cm
24mm
260KN
160KN
42Mpa
Hydraulic drive
35%
0-11
SAUER/REXROTH piston pump
SAUER/REXROTH piston motor

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Drive type	Dual wheel drive
Front axle load	7200kg
Rear axle load	4800kg
Steering System	
Туре	Articulated frame, hydraulic steering
Steering cylinder	Two cylinders
Steering pump	Gear pump
Working pressure	13MPa
Steering angle	±35°
Min. steering radius	7000mm ( outer side),5400mm (inner side)
Braking System	
Service brake	Oil-cut off braking
Parking brake	Hand operated drum brake
Dimensions	
Overall length	5820mm
Overall width	2278mm
Overall height	3050mm
Drum width	2100mm
Wheel base	3160mm
Drum Dia.	1570mm
Tyre size	23.1-26
Ground clearance	472mm
Service Capacities	
Hydrauclic tank	180L
Drive alxe central gear box	25L
Fuel tank	200L
Engine crank case	19L