

Single Drum Vibratory Roller LGR207 (Mechanical Transmission)

LGR207 is mostly worked in with the spread asphalt machine. Because of the very width vibrated wheel(1.7m) and the fine pressing speed which bring the great working ability. It is mostly worked with the largest spread asphalt. The roller is applied to built-road, parking area and industry area, it is especially suited for express shoulder, side walk and the limited area.

Engine	
Model	Xinchai 498
Туре	Vertical, water cooled, direct injection
Rated power	36.8KW
Rated speed	2000rpm
Rated fuel consumption	185g/kw•h
Main Technical Specification	
Operating weight	7000kg
Туре	Hydraulic vibration
Frequency	43Hz
Amplitude	0.4 mm
Static linear load	215N/cm
Dynamic linear load	320N/cm
Vertical oscillation	10°
Drum shell thickness	20mm
Centrifugal force	70KN
Transmission System	
Туре	Mechanical drive(gear box)
Grade ability	25%
Gear shifts(Forward/Reverse)	F3/R3
Traveling speed(km/h)	
Forward/Reverse I	2.2/2.2
Forward/Reverse II	4.7/4.7

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Forward/ReverseIII	15/15	
Axle		
Drive type	Rear wheel drive	
Front axle load	4000kg	
Rear axle load	3000kg	
Steering System		
Туре	Articulated frame, hydraulic steering	
Steering cylinder	Two cylinders	
Steering pump	Gear pump	
Working pressure	12MPa	
Steering angle	±36°	
Min. steering radius	5000mm (outer side),2870mm (inner side)	
Braking System		
Service brake	Disc brake, actuate rear wheels	
Parking brake	Hand operated drum brake	
Dimensions		
Overall length	5010mm	
Overall width	1880mm	
Overall height	2570mm	
Drum width	1700mm	
Wheel base	2750mm	
Drum Dia.	1220mm	
Tyre size	12.00-24	
Ground clearance	400mm	
Service Capacities		
Hydrauclic tank	110L	
Gear box	25L	
Drive alxe	25L	
Brake booster	10L	
Fuel tank	110L	
Engine crank case	16L	