

LGR212 Single Drum Vibratory Roller(Mechanical Transmission)

LGR212 single drum vibratory roller is equipped with YC6108G engine, PERMCO/HERCULES vibrating pump and motor, mechanical drive transmission, which is suitable for non-cohesive materials, such as sandy soil, gravel, crushed stones, rock fillings and slightly cohesive soils, designed for large foundation constructions such as high-class highways, mines, dams, airports, harbors, railways and industrial areas.

Engine	
Model	YC6108G
Туре	Vertical, water cooled, direct injection
Rated power	85KW
Rated speed	2000rpm
Rated fuel consumption	215g/kw∙h
Main Technical Specification	
Operating weight	12000kg
Туре	Hydraulic vibration
Frequency	30Hz
Amplitude	0.9/1.8mm
Static linear load	276N/cm
Vertical oscillation	8°
Drum shell thickness	24mm
Centrifugal force(high ampl.)	270KN
Centrifugal force(low ampl.)	140KN
Transmission System	
Туре	Mechanical drive(gear box)
Grade ability	35%

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Gear shifts(Forward/Reverse)	F3/R3
Traveling speed(km/h)	
Forward/Reverse I	1.8/1.8
Forward/Reverse II	3.7/3.7
Forward/ReverseIII	9.7/9.7
Axle	•
Drive type	Rear wheel drive
Front axle load	7200kg
Rear axle load	4800kg
Steering System	•
Туре	Articulated frame, hydraulic steering
Steering cylinder	Two cylinders
Steering pump	Gear pump
Working pressure	12MPa
Steering angle	±36°
Min. steering radius	7000mm (outer side),4870mm (inner side)
Braking System	•
Service brake	Disc brake, actuate rear wheels
Parking brake	Hand operated drum brake
Dimensions	
Overall length	5640mm
Overall width	2258mm
Overall height	2970mm
Drum width	2100mm
Wheel base	3080mm
Drum Dia.	1400mm
Tyre size	17.5-25
Ground clearance	360mm
Service Capacities	
Hydrauclic tank	150L
Gear box	25L
Drive alxe	25L
Brake booster	10L
Fuel tank	180L
Engine crank case	16L

Tel: +86-21-541-71571 Fax: +86-21-541-71572