

## **LGR216 Single Drum Vibratory Roller(Mechanical Transmission)**

LGR216 single drum vibratory roller is equipped with YC6108ZG engine, PERMCO/HERCULES vibrating pump and motor, mechanical drive transmission, which is suitable for non-cohesive materials, such as sandy soil, gravel, crushed stones, rock fillings and slightly cohesive soils, designed for large foundation constructions such as high-class highways, mines, dams, airports, harbors, railways and industrial areas. Cummins engine and pad foot shell as optional.

Engine	
Model	YC6108ZG
Туре	Vertical, water cooled, direct injection
Rated power	110KW
Rated speed	2000rpm
Rated fuel consumption	210g/kw⋅h
Main Technical Specification	
Operating weight	16000kg
Туре	Hydraulic vibration
Frequency	30Hz
Amplitude	1.8/0.9mm
Static linear load	378N/cm
Dynamic linear load	530N/cm
Vertical oscillation	8°
Drum shell thickness	32mm
Centrifugal force(high ampl.)	320KN
Centrifugal force(low ampl.)	180KN
Transmission System	
Туре	Mechanical drive(gear box)

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100 E-mail: <u>info@shlongji.com</u> Tel: +86-21-541-71571 Fax: +86-21-541-71572

Grade ability	35%
Gear shifts(Forward/Reverse)	F3/R3
Traveling speed(km/h)	
Forward/Reverse I	2/2
Forward/Reverse II	4/4
Forward/ReverseIII	10.5/10.5
Axle	<u> </u>
Drive type	Rear wheel drive
Front axle load	9600kg
Rear axle load	6400kg
Steering System	•
Туре	Articulated frame, hydraulic steering
Steering cylinder	Two cylinders
Steering pump	Gear pump
Working pressure	13MPa
Steering angle	±36°
Min. steering radius	7500mm ( outer side), 5400mm (inner side)
Braking System	·
Service brake	Disc brake, actuate rear wheels
Parking brake	Hand operated drum brake
Dimensions	·
Overall length	5820mm
Overall width	2278mm
Overall height	3000mm
Drum width	2130mm
Wheel base	3160mm
Drum Dia.	1570mm
Tyre size	23.1-26
Ground clearance	432mm
Service Capacities	
Hydrauclic tank	150L
Gear box	25L
Drive alxe	25L
Brake booster	10L
Fuel tank	180L
Engine crank case	18L

Tel: +86-21-541-71571 Fax: +86-21-541-71572