



Main technical specifications	unit	XMR30E
Operating weight	kg	3080
Distributed weight in vibration drum(front/rear)	kg	1240/1840
Static linear load(front/rear)	N/cm	121/180
Speed	km/h	0-7.5
Gradeability	%	20
min turning radius (out)	mm	4400
min ground clearance	mm	200
wheel base	mm	2150
steering angle		33
swing angle		10
vibration frequency	Hz	50
nominal amplitude	mm	0.5
centrifugal force	KN	30
drum diameter	mm	750
compacting width	mm	1000
Engine model		ZN385Q
Rated speed	r/min	2400

**Add:** Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

**Post Code:** 201100

**E-mail:** [info@shlongji.com](mailto:info@shlongji.com)

**Tel:** +86-21-541-71571

**Fax:** +86-21-541-71572

**Website:** [www.shlongji.com](http://www.shlongji.com) Wheel Loader,Road Roller,Dump Truck

Rated power	kw	21
Overall dimensions	mm	2900*1200*2760
Rated oil wear	g/kw.h	240
Fuel tank capacity	L	65
Hydraulic tank capacity	L	40
Sprinkler capacity	L	180

**Add:** Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

**Post Code:** 201100

**E-mail:** [info@shlongji.com](mailto:info@shlongji.com)

**Tel:** +86-21-541-71571

**Fax:** +86-21-541-71572

**Website:** [www.shlongji.com](http://www.shlongji.com) Wheel Loader,Road Roller,Dump Truck