

XCMG RP756 Road Paver



Items	Unit	Parameters
Basic paving width	m	3
Max. paving width	m	7.5
Max. paving thickness	mm	350
Paving speed	m/min	0~18
Travel speed	km/h	0~3.0
Theoretical Productivity	t/h	600
Hopper Capacity	t	14
Gradeability	%	20
Pavement evenness	mm/3m	3
Transverse levelling accuracy	%	±0.03
Centre crown ratio	%	-1~3

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Engine model		D6114ZG1B
Engine power	kw	140
Engine speed	r/min	2300
Fuel tank capacity	L	270
Machine weight	t	19.9~24.6
Dimension	mm	6700×3000×3850
Vibration frequency (optional)	Hz	0~50
Screed heating		Gas heating
Auger and conveyor control		Automatic Control by Ultrasonic Sensors
Automatic levelling control		Simulation control

Items	Unit
Screed model	575(RP802)
Type	Double vibrator, gas heating
Extension	Mechanical assembly
Width	0-1470r/min
Vibrator speed	3,5,7,9mm
Main amplitude	
Auxiliary amplitude	0,3,6,9,12mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572