

XCMG RP802 Road Paver



Item	Unit	RP802
Basic paving width	m	3
Max. paving width	m	8
Max. paving thickness	mm	380
Paving speed	m/min	0~14
Travel speed	km/h	0~3.0
Theoretical productivity	t/h	600
Hopper capacity	t	13
Gradeability	%	20
Pavement evenness	mm/3m	3
Cross slope error	%	±0.03
Crown adjustment range	%	0~3

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Diesel engine model		BF4M1013C
Diesel engine power	kw	118
Diesel engine speed	r/min	2300
Diesel oil tank capacity	L	230
Overall weight	t	16.5~23.5
Dimension	mm	6230×3000×3855
Vibration frequency	Hz	68~71
Screed heating mode		
Material level control mode		
Automatic Leveling Control		

Item	Unit
Screed model	575(RP802)
Type	Vibrating tamper, vibration, electrical heating
Stretch mode	Hydraulic stretch
Width range	3.0-8.0m
Vibrating tamper rotate speed	0-1500r/min
Vibration frequency	4mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572