## **XCMG G08ZZR Concrete Truck Mixer**



Туре	Model	Unit	G08ZZR
Performance of mixing drum	Geometric volume	m³	13.9
	Mixing volume	m³	8
	Maximum diameter of drum body	mm	2250
	Length of mixing drum	mm	4817
	Angle of inclination	0	13.5
	Rotating speed	r/min	0~14

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: <a href="www.shlongji.com">www.shlongji.com</a>
Tel: +86-21-541-71571
E-mail: <a href="mailto:info@shlongji.com">info@shlongji.com</a>
Fax: +86-21-541-71572

	Charge speed	m³/min	≥3
	Discharge speed	m³/min	≥2
	Residue ratio of discharge	%	<0.7
	Range of slump	cm	5~21
Hydraulic	Oil pump		international brand
	Motor		international brand
system	Reduction gears		international brand
	Hydraulic circuit		Closed type
	water tank capacity	L	450
Water supply	Way of water supply		Pneumatic
	Brand of chassis		Sinotruck
	Chassis model		ZZ1257N3847C(3625 wheel base) chassis of right-hand drive automobile
	Type of driving		Right-hand drive
Complete machine	Curb weight	kg	14000
	maximum gross	kg	25000
	Type of drive		6×4
	Wheel base	mm	3625+1350
	Tyre		12.00R20
	Means of power takeoff		Power takeoff by flywheel
	Notice model		XZJ5251GJB1
	External dimensions	(length×width×height)m m	9035×2500×3890

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: <a href="www.shlongji.com">www.shlongji.com</a>
Tel: +86-21-541-71571
E-mail: <a href="mailto:info@shlongji.com">info@shlongji.com</a>
Fax: +86-21-541-71572

## Longji Construction Machinery

## 上海龙基工程机械有限公司

Engine	Model		WD615.95E
	Rated power	Kw/r/min	247
	Displacement	L	9.726
	Emission standard		GB III

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: <a href="www.shlongji.com">www.shlongji.com</a>
Tel: +86-21-541-71571
E-mail: <a href="mailto:info@shlongji.com">info@shlongji.com</a>
Fax: +86-21-541-71572