

XCMG G10NX1 Concrete Truck Mixer



Type	Model	Unit	G10NX1
Performance of mixing drum	Geometric volume	m ³	17.1
	Mixing volume	m ³	10
	Maximum diameter of drum body	mm	2380
	Length of mixing drum	mm	5447
	Angle of inclination	°	13.5
	Rotating speed	r/min	0~14
	Charge speed	m ³ /min	≥3
	Discharge speed	m ³ /min	≥2
	Residue ratio of	%	<0.7

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	discharge		
	Range of slump	cm	5~21
Hydraulic system	Oil pump		international brand
	Motor		international brand
	Reduction gears		international brand
	Hydraulic circuit		Closed type
Water supply	water tank capacity	L	450
	Way of water supply		Pneumatic
Complete machine	Brand of chassis		XCMG NAC
	Chassis model		NXG3251D3DKCX
	Type of driving		Left-hand drive
	Curb weight	kg	14000
	maximum gross weight	kg	25000
	Driving type		6×4
	Wheel base	mm	3850+1350
	Tyre		12.00R20
	Means of power takeoff		Power takeoff by flywheel
	Notice model		
	External dimensions	(length×width×height)m m	
Engine	Model		WP10.336N/WP10.340E3 2
	Rated power	Kw/r/min	247
	Displacement	L	9.726
	Emission standard		GB III

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572