XCMG G12NX Concrete Truck Mixer



Туре	Model	Unit	G12NX
Performance of mixing drum	Geometric volume	m³	19.5
	Mixing volume	m³	12
	Maximum diameter of drum body	mm	2380
	Length of mixing drum	mm	5967
	Angle of inclination	0	11
	Rotating speed	r/min	0~14
	Charge speed	m³/min	≥3
	Discharge speed	m³/min	≥2
	Residue ratio of	%	<0.7

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com
Tel: +86-21-541-71571
E-mail: info@shlongji.com
Fax: +86-21-541-71572

	discharge		
	Range of slump	cm	5~21
Hydraulic system	Oil pump		international brand
	Motor		international brand
	Reduction gears		international brand
	Hydraulic circuit		Closed type
Water supply	water tank capacity	L	450
	Way of water supply		Pneumatic
	Brand of chassis		NAC
	Chassis model		NXG3250D3KCLX
	Type of driving		Left-hand drive
	Curb weight	kg	15200
Complete machine	maximum gross weight	kg	25000
	Type of drive		6×4
	Wheel base	mm	4000+1350
	Tyre		12.00R20
	Means of power takeoff		Power takeoff by flywheel
	Notice model		
	External dimensions	(length×width×height)m	9900×2500×3995
Engine	Model		WP10.336N/WP10.340E3
	Rated power	Kw/r/min	247
	Displacement	L	9.726
	Emission standard		GB III

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com
Tel: +86-21-541-71571
E-mail: info@shlongji.com
Fax: +86-21-541-71572