

XCMG G12SQL Concrete Truck Mixer



| Type | Model | Unit | G12SQL |
|----------------------------|-------------------------------|---------------------|--------|
| Performance of mixing drum | Geometric volume | m ³ | 19.5 |
| | Mixing volume | m ³ | 12 |
| | Maximum diameter of drum body | mm | 2380 |
| | Length of mixing drum | mm | 5967 |
| | Angle of inclination | ° | 12 |
| | Rotating speed | r/min | 0~14 |
| | Charge speed | m ³ /min | ≥3 |
| | Discharge speed | m ³ /min | ≥2 |
| | Residue ratio of | % | <0.7 |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

| | | | |
|------------------|------------------------|-----------------------------|---------------------------|
| | discharge | | |
| | Range of slump | cm | 5~21 |
| Hydraulic system | Oil pump | | international brand |
| | Motor | | international brand |
| | Reduction gears | | international brand |
| | Hydraulic circuit | | Closed type |
| Water supply | water tank capacity | L | 450 |
| | Way of water supply | | Pneumatic |
| Complete machine | Brand of chassis | | C&C Trucks |
| | Chassis model | | SQR3251N6T4-E1 |
| | Type of driving | | Left-hand drive |
| | Curb weight | kg | |
| | maximum gross weight | kg | 25000 |
| | Type of drive | | 6×4 |
| | Wheel base | mm | 4200+1350 |
| | Tyre | | 12.00R20 |
| | Means of power takeoff | | Power takeoff by flywheel |
| | Notice model | | |
| | External dimensions | (length×width×height)m m | 10055×2500×3995 |
| | | | |
| Engine | Model | | |
| | Rated power | Kw/r/min | 250 |
| | Displacement | L | 9.726 |
| | Emission standard | | GB IV |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572