XCMG G12SX Concrete Truck Mixer



Туре	Model	Unit	G12SX
Performance of mixing drum	Geometric volume	m³	19.5
	Mixing volume	m³	12
	Maximum diameter of drum body	mm	2380
	Length of mixing drum	mm	5967
	Angle of inclination	0	12
	Rotating speed	r/min	0~14
	Charge speed	m³/min	≥3
	Discharge speed	m³/min	≥2
	Residue ratio of discharge	%	<0.7

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com
Tel: +86-21-541-71571
E-mail: info@shlongji.com
Fax: +86-21-541-71572

	I		
	Range of slump	cm	5~21
	Oil pump		international brand
	Motor		international brand
Hydraulic system	Reduction gears		international brand
	Hydraulic circuit		Closed type
Water supply	water tank capacity	L	450
	Way of water supply		Pneumatic
	Brand of chassis		XCQC
	Chassis model		SX5255GJBJR404
	Type of driving		Left-hand drive
	Curb weight	kg	14600
Complete machine	maximum gross weight	kg	25000
	Type of drive		6×4
	Wheel base	mm	3975+1400
	Tyre		12.00R20
	Means of power takeoff		Power takeoff by flywheel
	Notice model		XZJ5250GJB2
	External dimensions	(length×width×height)m	9850×2500×3980
Engine Model Rated power Kw/r/min	Model		WP10.336
	Rated power	Kw/r/min	247
	L	9.726	
	Emission standard		GB III

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com
Tel: +86-21-541-71571
E-mail: info@shlongji.com
Fax: +86-21-541-71572