

XCMG GD08F8 Concrete Truck Mixer



Type	Model	Unit	GD08FD
Performance of mixing drum	Geometric volume	m ³	14.3
	Mixing volume	m ³	8
	Maximum diameter of drum body	mm	2280
	Length of mixing drum	mm	4624
	Angle of inclination	°	13
	Rotating speed	r/min	0~14
	Charge speed	m ³ /min	≥3
	Discharge speed	m ³ /min	≥2
	Residue ratio of	%	<0.7

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	discharge		
	Range of slump	cm	5~21
Hydraulic system	Oil pump		international brand
	Motor		international brand
	Reduction gears		international brand
	Hydraulic circuit		Closed type
Water supply	water tank capacity	L	450
	Way of water supply		Pneumatic
Complete machine	Brand of chassis		Ford
	Chassis model		Cargo 2629
	Type of driving		Left-hand drive
	Curb weight	kg	
	maximum gross weight	kg	2300
	Type of drive		6×4
	Wheel base	mm	3440+1360
	Tyre		12.00R20
	Means of power takeoff		Power takeoff by flywheel
	Notice model		
	External dimensions	(length×width×height)m m	8680×2455×3920
Engine	Model		Cummins ISB6.7
	Rated power	Kw/r/min	213
	Displacement	L	6.693
	Emission standard		Euro V

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572