

XCMG QUY 350 Crawler Crane



Item		Unit	Data
Max. lifting capacity		t	350
Standard working condition	Heavy boom length	m	24-84/350
	Light boom length	m	42-102/190
	Fixed Jib length	m	12-36/80
	Tower attachment length	m	24-72/165

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Standard superlift working condition	Heavy boom length	m	36-84/350
	Light boom length	m	78-120/190
	Fixed Jib length	m	12-36/80
	Tower attachment length	m	24-72/190
Max. single line hoisting speed(with no load,at 6th layer)		m/min	130
Max. single line speed for boom elevating system(with no load,at 6th layer)		m/min	44×2
Max. single line speed for tower attachment elevating system(with no load,at 6th layer)		m/min	110
Max. single line speed for sideways superlift elevating system (with no load,at 6th layer)		m/min	110
Swing speed		r/min	1.0
Propel speed		km/h	0.95
Mean ground pressure		MPa	0.13
Engine output		kW	310
Total mass (with 350t hook block,24m heavy boom)		t	325
Max. weight of single part(main machine) in transport state		t	55
Dimension of single part(main machine) in transport state(L×W×H)		m	10.36×3.4×3.0

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572