XCMG QUY 650 Crawler Crane



Item		Unit	Data
Max. lifting capacity		t	650
Standard working condition	Heavy boom length	m	24-84
	Light boom length	m	66-102
	Fixed Jib length	m	12-36
	Tower attachment length	m	24-84
Standard superlift working	Heavy boom length	m	36-96
	Light boom length	m	90-138
	Fixed Jib length	m	12
	Tower attachment length	m	24-96

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100Website: www.shlongji.comE-mail: info@shlongji.comFax: +86-21-541-71572

Longji Construction Machinery

Max. single line hoisting speed(with no load,at 6th layer)	m/min	130
Max. single line speed for boom elevating system(with no load,at 6th layer)	m/min	58×2
Max. single line speed for tower attachment elevating system(with no load, at 6th layer)	m/min	115
Max. single line speed for sideways superlift elevating system (with no load,at 6th layer)	m/min	115
Swing speed	r/min	0.65
Propel speed	km/h	1.0
Mean ground pressure	MPa	0.146
Engine output	kW	494
Total mass (with 650t hook block,24m heavy boom)	t	530
Max. weight of single part(main machine) in transport state	t	74
Dimension of single part(main machine) in transport state(L×W×H)	m	12.6×3.4×3.4