

Shantui SD13S Bulldozer



MODEL	SD13S
L×W×H (Ripper not included)	4492×3450×3000
Operating weight (Ripper not included)	14.9
Engine	Shangchai SC8D143G2B1
Rated power	95.5/1900
Gradeability	30
Blade type	Straight tilt blade
Blade width	3450×980
Dozing capacity	3.3
Ma× drop below ground of blade	590
Lift height of blade	930
Ripper type	-
Ripping depth of ripper	-

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Lifting height of ripper	-
Number of carriers (each side)	2
Number of track rollers (each side)	6
Number of track shoes (each side)	38
Width of track shoe	700
Track gauge	1880
Ground length and ground pressure	2365-0.044
Pitch	190
Forward speed	0 - 3.2
	0 - 5.9
	0 - 9.8
Reverse speed	0 - 3.9
	0 - 7.1
	0 - 11.9

- The extended track ensures low ground pressure, high reliability and strong traction, contributing to precise operation;
- The power shift transmission not only ensures smooth power shift, but also reaches target speeds and carries out directional transfers with a single control lever;
- The wet steering clutch and brake can extend service life. They work interactively, ensuring quick and flexible steering operations;
- The single control lever can control all blade actions;
- The drift sealing in the drive wheel, track roller and carrier roller can prevent dust from entering the track system, as well as lubricant leakage, thereby ensuring a long service life;
- The hexahedron cab features wide visibility, and the insulation materials in the cab can reduce noise and vibrations;
- The spin type fuel filter and dust separator, the air filters and the other filtration devices can prolong work time and reduce service time;
- The comfortable cab seat can adjust upward and downward, forward and backward, meeting any positional needs the operator may have;
- Side engine operation and the combination of a drive/brake operation system and foot brake makes overall operation of the bulldozer more rapid and convenient.

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572